Shortname: PROFOZ

Longname: OMI/Aura Vertical Ozone (03) Profile 1-Orbit L2 Swath

13x48 km

PFS Version: 0.9.3

Date: 27 July 2010

Author(s): Kai Yang (UMBC), Xiong Liu (UMBC), Pawan K. Bhartia

(NASA)

PGE Version: 0.9.3 and later

Lead Algorithm Scientist: Xiong Liu, Kai Yang, Kelly Chance, Pawan K.

Bhartia

Lead Algorithm Developer: Xiong Liu, Kai Yang, Thomas P. Kurosu

Lead PGE Developer: Kai Yang, Xiong Liu

PGE Developer(s): OMI SIPS

Description: >

This document specifies the product format for the Version 0.9.3 and subsequent delivery of the PROFOZ L2 PGE which uses OMI UV (both UV-1 and UV-2) measurements (Ref 1) to retrieve vertical ozone profile and other parameters. The product is stored as one HDF-EOS 5 swath file for each granule (i.e., one orbit) of PROFOZ L2 data, and has a size of xxx Mb.

Global Metadata:

- Metadata Name: AlgorithmName

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE

Description: Actual is "PROFOZ"

- Metadata Name: AlgorithmVersion

Mandatory: T

Data Type: HE5T NATIVE CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE

Description: Actual is "Version 0.9.3"

- Metadata Name: AuthorAffiliation

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PCF

Description: Actual is "GEST/UMBC and GSFC/NASA"

- Metadata Name: AuthorName

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PCF
Description: >

Actual is "Xiong Liu, Kai Yang, Pawan K. Bhartia"

- Metadata Name: GranuleDay

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: Range is 1 to 31.

Data Source: PGE
Description: >

The day of the month at the start of the granule.

- Metadata Name: GranuleJulianDay

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: Range is 1 to 365.

Data Source: PGE
Description: >

The Julian day of the year at the start of the granule.

- Metadata Name: GranuleMonth

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: Range is 1 to 12.

Data Source: PGE

Description: The month at the start of the granule.

- Metadata Name: GranuleYear

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: Range is 2000 to 2099.

Data Source: PGE Description: >

The (four-digit) year at the start of the granule.

- Metadata Name: HDFEOSVersion

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Automatically set by HDF-EOS.

Data Source: HE

Description: Example is "HDFEOS_5.1.5".

- Metadata Name: InputVersions

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE Description: >

A list of every ESDT (including version) whose product was used as

input for the processing.

- Metadata Name: InstrumentName

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Valids are "HIRDLS", "MLS", "OMI" and "TES".

Data Source: PCF

Description: Actual is "OMI" (see Section 6.1 of Reference

2).

- Metadata Name: OrbitData

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Valids are "DEFINITIVE" and "PREDICTED".

Data Source: L1B
Description: >

Indicates whether orbit data used by the L1B processor is

definitive

or predicted.

- Metadata Name: OrbitNumber

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: Range is 1 to 999999.

Data Source: PGE

Description: OMI Orbit number.

- Metadata Name: PGEVERSION

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Range is "0.0.0" to "9.9.99".

Data Source: PCF

Description: Actual is "0.9.3".

- Metadata Name: ProcessingCenter

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PCF

Description: Example is "OMIDAPS".

- Metadata Name: ProcessingHost

Mandatory:

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PCF Description: >

The output from executing the Unix "uname -a" command on the

processing machine.

- Metadata Name: ProcessLevel

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Valids are "1b", "2" and "3".

Data Source: PCF

Description: Actual is "2".

- Metadata Name: TAI93At0z0fGranule

Mandatory: T

Data Type: HE5T_NATIVE_DOUBLE

Number of Values: 1

Range or Valids: Range is 0.0d+00 to 1.0d+30.

Data Source: PGE Description: >

The TAI93 time at 0z of the granule (see Section 6.1 of Reference

2).

Metadata Name: TAI93StartOfGranule

Mandatory: T

Data Type: HE5T NATIVE DOUBLE

Number of Values: 1

Range or Valids: Range is 0.0d+00 to 1.0d+30.

Data Source: PGE
Description: >

The TAI93 time at the start of granule (see Section 6.1 of

Reference 2).

- Metadata Name: SpectralDomainControls

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE

Description: >

Switches used in the algorithm (set by defaut or inputs) that controls

spectral channels used in the retrievals, such as the number of channels,

their wavelength ranges, or if spectral coadding is performed.

- Metadata Name: SlitControls

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE Description: >

Switches used in the algorithm (set by defaut or inputs) that controls

slit functions used in the retrievals, such as the type of the slit, and

or if the slit widths change with wavelength.

Metadata Name: WavelengthCalibrationControls

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE Description: >

Switches used in the algorithm (set by defaut or inputs) that controls

wavelength calibration done in the retrievals, such as if calibration

is performed before retrieval, or before coadding, or if solar wavelength

calibration is performed.

- Metadata Name: ProcessingControls

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE Description: >

Switches used in the algorithm (set by defaut or inputs) that controls

how processing is done in the retrievals.

- Metadata Name: L1_RadianceFilename

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE

Description: Example is "./OMI-Aura_L1-

OML1BRUG_2006m0711t2226-o10582_v003-2007m0515t122953.he4".

- Metadata Name: L2 CloudFilename

Mandatory:

Data Type: HE5T NATIVE CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE

Description: Example is "./OMI-Aura_L2-

OMCLD02_2006m0711t2226-o10582_v003-2007m1130t190603.he5".

- Metadata Name: FitVariableNames

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE
Description: >

Names of fitting variables used in the retrieval algorithm.

- Metadata Name: OtherGasNames

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE
Description: >

Names of Other (non-ozone) trace gases used in the retrieval algorithm.

- Metadata Name: NonGasVariableNames

Mandatory: T

Data Type: HE5T NATIVE CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE Description: >

Names of non-gas fitting varialbles used in the retrieval

algorithm.

- Metadata Name: NonGasVariableUnits

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE Description: >

Units of non-gas fitting variables used in the retrieval algorithm.

Swath Metadata:

- Metadata Name: SwathName

Mandatory: T

Data Type: HE5T NATIVE CHAR

Number of Values: 1

Range or Valids: Valid is "OMI Vertical Ozone Profile"

Data Source: PGE

Description: Actual is "OMI Vertical Ozone Profile"

- Metadata Name: VerticalCoordinate

Mandatory: T

Data Type: HE5T_NATIVE_CHAR

Number of Values: 1
Range or Valids: >

Valids are "Pressure", "Altitude", "Potential Temperature",

"Partial Column" and "Total Column".

Data Source: PGE Description: >

Actual is "Partial Column" (see Section 6.2 of Reference 2).

- Metadata Name: nXtrack

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 30 Data Source: PGE

Description: Number of cross-track pixels in the output

- Metadata Name: nXtrackp1

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 2 to 31
Data Source: PGE

Description: Number of cross track pixels plus 1

- Metadata Name: nTimes

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 1700

Data Source: PGE

Description: Number of along-track scan lines in the output

- Metadata Name: nTimesp1

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 1700

Data Source: PGE

Description: Number of along-track scan lines plus 1 in the

output

- Metadata Name: nLayer

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 101

Data Source: PGE

Description: Number of vertical layers used in the

retrievals.

Ozone values are given at each layer.

- Metadata Name: nLayerp1

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 2 to 102

Data Source: PGE

Description: Number of vertical levels used in the

retrievals.

It equals to nLayer + 1. Atmosospheric profiles

of

pressure, altitude, temperature are provided at

each level.

- Metadata Name: nElms

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 65535

Data Source: PGE

Description: Number of elements in the upper triangle

(exclude the

diagonal) of the ozone noise covariance matrix.

The size

of the ozone noise covariance matrix is nLayer x

nLayer,

so the nElms = (nLayer*(nLayer-1))/2.

- Metadata Name: nFitvar

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 200

Data Source: PGE

Description: Number of fitting variables (nfitvar = nLayer + nParameter + nGas) used in the retrievals.

- Metadata Name: nParameter

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 200
Data Source: PGE

Description: Number of fitting variables, exlcuding (both

ozone and other) trace gas variables used in the retrievals.

- Metadata Name: nWavelMax

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 600

Data Source: PGE

Description: Maximum number of fitting wavelengths used in

the

retrievals. Set to -1 when FitSpecta,

SimRadiance, and

Wavelength are not written to the output file.

- Metadata Name: nChannel

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 254
Data Source: PGE

Description: Number of spectral channels used in the

retrievals.

- Metadata Name: nGas
 Mandatory: T

Data Type: HE5T NATIVE INT

Number of Values: 1

Range or Valids: 1 to 254

Data Source: PGE

Description: Number of trace gases (other than ozone)

retrieved.

- Metadata Name: nXtrackMax

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 60 Data Source: PGE

Description: Maximum number of cross-track pixels.

- Metadata Name: nTimesMax

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 2000

Data Source: PGE

Description: Maximum number of along-track scan lines.

- Metadata Name: XOffset

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 30 Data Source: PGE

Description: Start pixel in the cross-track direction.

- Metadata Name: YOffset

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 0 to 60 Data Source: PGE

Description: Start scan line in the along-track direction.

- Metadata Name: nXbin

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 0 to 60 Data Source: PGE

Description: Number of pixels spatially coadded in the cross-

track direction.

- Metadata Name: nYbin

Mandatory: T

Data Type: HE5T NATIVE INT

Number of Values: 1

Range or Valids: 0 to 60 Data Source: PGE

Description: Number of pixels spatially coadded in the along-

track direction.

- Metadata Name: NumTimes

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 2000

Data Source: PGE

Description: number of uncoadded along-track scan lines in

the full granule.

- Metadata Name: NumTimesSmallPixel

Mandatory: T

Data Type: HE5T_NATIVE_INT

Number of Values: 1

Range or Valids: 1 to 100000

Data Source: PGE

Description: number of along-track small pixels in the full

granule.

- Metadata Name: EarthSunDistance

Mandatory: T

Data Type: HE5T_NATIVE_FLOAT

Number of Values: 1

Range or Valids: 1 to 2.0e15

Data Source: PGE

Description: Earth-Sun distance.

Swath Dimensions:

- Dimension Name: nTimes

Data Type: HE5T_NATIVE_INT

Dimension Type: FIXED Number of Values: 1

Range or Valids: Range is 0 to 9999.

Data Source: L1B

Description: Number of along-track scan lines in the output.

- Dimension Name: nXtrack

Data Type: HE5T NATIVE INT

Dimension Type: FIXED Number of Values: 1

Range or Valids: Range is 1 to 60.

Data Source: L1B

Description: Number of cross-track scan pixels in the output.

Geolocation Fields:

Field Name: GroundPixelQualityFlags

Data Type: HE5T_NATIVE_UINT16
Dimensions: nTimes,nXtrack

Range or Valids: Range is 0 to 65534.

Missing Value: 65535
Offset: 0.0d0
Scale Factor: 1.0d0
Units: NoUnits
Data Source: L1B

Title: "Ground Pixel Quality Flags"

Unique Field Definition: TOMS-OMI-Shared

Description: >

```
Bits 0 to 3 together contain the land/water flags:
         shallow ocean
    0
         land
     1

    shallow inland water

         - ocean coastline/lake shoreline
         ephemeral (intermittent) water
         deep inland water

    continental shelf ocean

     7
         deep ocean
     8-14 – not used
         error flag for land/water
  Bits 4 to 6 are flags that are set to 0 for FALSE, or 1 for TRUE:
    Bit 4 - sun glint possibility flag
    Bit 5 - solar eclipse possibility flag
    Bit 6 - geolocation error flag
  Bit 7 is reserved for future use (currently set to 0).
   Bits 8 to 14 together contain the snow/ice flags (based on NISE):
            snow-free land
     1-100
            - sea ice concentration (percent)
     101

    permanent ice (Greenland, Antarctica)

     102
            not used
            dry snow
     103
            - ocean (NISE-255)
     104
     105-123 - reserved for future use
         mixed pixels at coastline (NISE-252)
     124
     125
           suspect ice value (NISE-253)
    126
           corners undefined (NISE-254)
     127
            - error
  Bit 15 - NISE nearest neighbor filling flag.
   (See Section 6.2 of Reference 4 for more details.)
- Field Name:
                            Latitude
 Data Type:
                            HE5T NATIVE FLOAT
 Dimensions:
                            nTimes, nXtrack
 Range or Valids:
                            Range is -90.0 to 90.0.
 Missing Value:
                            "-0X1P+100 (C language representation)"
 Offset:
                            0.0d+00
 Scale Factor:
                            1.0d+00
 Units:
                            deg
 Data Source:
                            L<sub>1</sub>B
                            "Geodetic Latitude of a Pixel Center"
 Title:
 Unique Field Definition: TOMS-Aura-Shared
 Description: >
  The geodetic latitude (in deg) at the center of the ground pixel.
- Field Name:
                            LatitudePixelCorner
```

Data Type: HE5T_NATIVE_FL0AT
Dimensions: nTimesp1,nXtrackp1
Page of Valida: Dange is 00 0 to 0

Range or Valids: Range is -90.0 to 90.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: deg
Data Source: PGE

Title: "Geodetic Corner Latitude"

Unique Field Definition: TOMS-Aura-Shared

Description: Geodetic Latitude of pixel corners,

assuming no overlapping between pixels.

- Field Name: Longitude

Data Type: HE5T_NATIVE_FLOAT Dimensions: nTimes,nXtrack

Range or Valids: Range is -180.0 to 180.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: deg
Data Source: L1B

Title: "Geodetic Longitude of a Pixel Center"

Unique Field Definition: TOMS-Aura-Shared

Description: >

The geodetic longitude (in deg) at the center of the ground pixel.

- Field Name: LongitudePixelCorner
Data Type: HE5T_NATIVE_FLOAT
Dimensions: nTimesp1,nXtrackp1
Range or Valids: Range is -90.0 to 90.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: deg
Data Source: PGE

Title: "Geodetic Corner Longitude"

Unique Field Definition: TOMS-Aura-Shared

Description: Geodetic Longitude of pixel corners,

assuming no overlapping between pixels.

- Field Name: RelativeAzimuthAngle
Data Type: HE5T_NATIVE_FL0AT
Dimensions: nTimes,nXtrack

Range or Valids: Range is -180.0 to 180.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: deg(EastofNorth)

Data Source: L1B

Title: >

"Relative Azimuth Angle (sun+180-view) East of North"

Unique Field Definition: TOMS-Aura-Shared

Description: >

The relative (sun + 180 - view) azimuth angle (in deg) for the ground pixel.

- Field Name: SecondsInDay

Data Type: HE5T_NATIVE_FLOAT

Dimensions: nTimes

Range or Valids: Range is 0.0 to 86401.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: s Data Source: L1B

Title: "Seconds after UTC Midnight"

Unique Field Definition: TOMS-Aura-Shared

Description: >

The time (in s) after UTC midnight at the start of the scan.

- Field Name: SolarZenithAngle
Data Type: HE5T_NATIVE_FLOAT
Dimensions: nTimes,nXtrack

Range or Valids: Range is 0.0 to 180.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: deg
Data Source: L1B

Title: "Solar Zenith Angle" Unique Field Definition: TOMS-Aura-Shared

Description: >

The solar zenith angle (in deg) for the ground pixel.

- Field Name: SpacecraftAltitude
 Data Type: HE5T NATIVE FLOAT

Dimensions: nTimes

Range or Valids: Range is 4.0E05 to 9.0E05.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00

Units: m Data Source: L1B

Title: "Spacecraft Altitude" Unique Field Definition: TOMS-Aura-Shared

Description: >

Height above WGS84 ellipsoid.

- Field Name: SpacecraftLatitude

Data Type: HE5T_NATIVE_FLOAT

Dimensions: nTimes

Range or Valids: Range is -90.0 to 90.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: deg
Data Source: L1B

Title: "Spacecraft Latitude"

Unique Field Definition: TOMS-Aura-Shared

Description: >

Geodetic latitude above WGS84 ellipsoid.

- Field Name: SpacecraftLongitude
 Data Type: HE5T_NATIVE_FLOAT

Dimensions: nTimes

Range or Valids: Range is -180.0 to 180.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: deg
Data Source: L1B

Title: "Spacecraft Longitude"

Unique Field Definition: TOMS-Aura-Shared

Description: >

Geodetic longitude above WGS84 ellipsoid.

- Field Name: Time

Data Type: HE5T_NATIVE_DOUBLE

Dimensions: nTimes

Range or Valids: Range is -5.0D09 to 1.0D10.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: s Data Source: L1B

Title: "Time at Start of Scan (TAI93)"

Unique Field Definition: TOMS-Aura-Shared

Description: >

The TAI93 time (in s) at the start of the scan.

- Field Name: ViewingZenithAngle
Data Type: HE5T_NATIVE_FLOAT
Dimensions: nTimes,nXtrack

Range or Valids: Range is 0.0 to 70.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: deg
Data Source: L1B

Title: "Viewing Zenith Angle"

Unique Field Definition: TOMS-Aura-Shared

Description: >

The viewing zenith angle (in deg) for the ground pixel.

Data Fields:

- Field Name: AerosolIndex

Data Type: HE5T_NATIVE_FLOAT Dimensions: nXtrack,nTimes

Range or Valids: Range is -200 to 200

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "UV Aerosol Index"

Unique Field Definition: OMI-Specific

Description: Aerosol Index dervied from UV2 fitting

window (from \sim 310 to \sim 330 nm).

- Field Name: AverageResiduals
 Data Type: HE5T_NATIVE_FLOAT

Dimensions: nChannel,nXtrack,nTimes Range or Valids: Range is 0 to 1.0E4.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: %, percent

Data Source: PGE

Title: "Average Fitting Residuals (percent)"

Unique Field Definition: OMI-Specific

Description: Average radiance fitting residuals

(percent) for each fitting channel.

- Field Name: CloudFlag

Data Type: HE5T_NATIVE_UINT8
Dimensions: nXtrack,nTimes
Range or Valids: Range is 0 to 4.

Missing Value: 255
Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Cloud Flag" Unique Field Definition: OMI-Specific

Description: >

Cloud Flag, 0: OMCLDRR cloud-top pressure 1: OMCLDO2 cloud-top pressure

2: OMCLDRR climatological cloud-top pressure

3: adjusted cloud-top pressure (Lambertian clouds:

20 hPa

above surface pressure, Mie clouds: cloud 20 hPa

above surface,

cloud thickness is assumed 100 hPa per 20 cloud

optical thickness)

Range or Valids: Range is -0.1 to 1.1.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Effective Cloud Fraction"

Unique Field Definition: OMI-Specific

Description: Effective cloud fraction fitted in the

retrievals.

Range or Valids: Range is 90 to 1013.25 hPa.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: hPa
Data Source: PGE

Title: "Effective Cloud-Top Pressure"

Unique Field Definition: OMI-Specific

Description: Effective Cloud-Top Pressure.

- Field Name: ExitStatus
Data Type: HE5T_NATIVE_INT8

Data Type: HE51_NATIVE_INT8
Dimensions: nXtrack,nTimes

Range or Valids: Range is -10 to 110.

Missing Value: -127
Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Retrieval Exit Status"

Unique Field Definition: OMI-Specific

Description: Retrieval exit status:

1, converge in cost function between two iterations after LIDORT run

 $\,$ 2, converge in cost function after parameter updates with weighting functions

```
4, converge in ozone parameters
        3, 1 + 2
        5, 1 + 4
        6, 2 + 4
        7.1 + 2 + 4
        if negative values occur for the last iteration, add + 100
        0, not converge
        -1, failure due to set cldalb
        -2, failure due atmospheric input preparation
        -3, failure due to too small/large (usually large negative)
ozone values
        -4, failure in computing Ring spectra
        -5, failure due to LIDORt calculation
        -6, failure due to the occurrence of NaN values
 - Field Name:
                             FitSpectra
   Data Type:
                             HE5T NATIVE FLOAT
                             nWavelMax,nXtrack,nTimes
   Dimensions:
   Range or Valids:
                             Range is 0 to 1.0.
                             "-0X1P+100 (C language representation)"
   Missing Value:
   Offset:
                             0.0d+00
   Scale Factor:
                             1.0d+00
   Units:
                             NoUnits
   Data Source:
                             PGE
                             "Observed Normalized Radiance: I/F"
   Title:
   Unique Field Definition:
                             OMI-Specific
   Description:
                             Observed normalized radiance: I/F. This
is an
      optional datafield, which means it may not be present in the
output.
      If nWavelMax = -1 in swath attribute, or it is not listed as one
of the
      swath dimensions, this data field is not in the output file.
 - Field Name:
                             GlintProbability
   Data Type:
                             HE5T NATIVE FLOAT
   Dimensions:
                             nXtrack,nTimes
   Range or Valids:
                             Range is 0 to 1.0.
   Missing Value:
                             "-0X1P+100 (C language representation)"
   Offset:
                             0.0d+00
   Scale Factor:
                             1.0d+00
   Units:
                             %, precent
   Data Source:
                             PGE
                             "Glint Probability"
   Title:
   Unique Field Definition:
                             OMI-Specific
   Description:
                             The possibility of glint probability
(based on viewing geometry).
 - Field Name:
                             MeasurementQualityFlags
```

Data Type: HE5T_NATIVE_UINT8

Dimensions: nTimes

Range or Valids: Range is 0 to 254.

Missing Value: 255
Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Measurement Quality Flags"

Unique Field Definition: OMI-Specific

Description: >

The measurement quality flag associated with each scan line (Bit value

is 0 for not set and 1 for set):

Bit 1 - Measurement Error Flag: Any of L1B

MeasurementQualityFlags bit 0,

1 or 3 are set for radiance or solar product used.

Bit 2 - Measurement Warning Flag: Any of L1B

MeasurementQualityFlags

used.

bit 2, 4, 5, 8, 9 are set for radiance or solar product

Bit 3 - Rebinned Measurement Flag: L1B radiance MeasurementQualityFlags

bit 7 is set.

Bit 4 - SAA Flag: L1B MeasurementQualityFlags bit 10 is set for radiance

or solar product used.

Bit 5 - Spacecraft Maneuver Flag: L1B MeasurementQualityFlags bit 11 is

set for radiance or solar product used.

Bit 6 — Instrument Setting Error Flag: Values for Earth and solar

InstrumentConfigurationId are not compatible.

Bit 7 - Ascending/Descending flag: $0 \Rightarrow$ Ascending; $1 \Rightarrow$ Descending

- Field Name: NonGasParameterAPriori

Data Type: HE5T_NATIVE_FLOAT

Dimensions: nParameter,nXtrack,nTimes Range or Valids: Range is -1e+20 to 1e+20.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: Specific to Each Parameter

Data Source: PGE

Title: "A Priori for Non-Gas Variables"

Unique Field Definition: OMI-Specific

Description: A priori for non-gas fitting variables.

- Field Name: NonGasParameterAPrioriError

Data Type: HE5T_NATIVE_FLOAT

Dimensions: nParameter,nXtrack,nTimes Range or Valids: Range is -1e+20 to 1e+20.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: Specific to Each Parameter

Data Source: PGE

Title: "A Priori Error for non-Gas Fitting

Variables"

Unique Field Definition: OMI-Specific

Description: A priori error for non-gas fitting

variables.

- Field Name: NonGasParameterRetrieved

Data Type: HE5T_NATIVE_FLOAT

Dimensions: nParameter,nXtrack,nTimes Range or Valids: Range is -1e+20 to 1e+20.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: Specific to Each Parameter

Data Source: PGE

Title: "Retrievals for Non-Gas Fitting

Variables"

Unique Field Definition: OMI-Specific

Description: Retrieved values for non-gas fitting

variables.

- Field Name: NonGasParameterRetrievedPrecision

Data Type: HE5T_NATIVE_FLOAT

Dimensions: nParameter,nXtrack,nTimes
Range or Valids: Range is -1e+20 to 1e+20.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: Specific to Each Parameter

Data Source: PGE

Title: "Retrieval Precision in for non-Gas

Fitting Variables"

Unique Field Definition: OMI-Specific

Description: Retrieval precision in non-gas fitting

variables.

- Field Name: NonGasParameterRetrievedSolutionError

Data Type: HE5T_NATIVE_FLOAT

Dimensions: nParameter,nXtrack,nTimes Range or Valids: Range is -1e+20 to 1e+20.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: Specific to Each Parameter

Data Source: PGE

Title: "Retrieval Solution Errors in Non-Gas

Variables"

Unique Field Definition: OMI-Specific

Description: Retrieval solution errors (root sum

square of random-noise

and smoothing errors) for non-gas fitting

variables.

- Field Name: 03APrioriProfile
Data Type: HE5T_NATIVE_FL0AT
Dimensions: nLayer,nXtrack,nTimes
Range or Valids: Range is 0 to 100.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "A Priori Ozone Profile"

Unique Field Definition: OMI-Specific

Description: A priori ozone profile.

Field Name: 03APrioriProfileError
 Data Type: HE5T_NATIVE_FLOAT
 Dimensions: nLayer,nXtrack,nTimes
 Range or Valids: Range is 0 to 100.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "A Priori Error in Ozone Profile"

Unique Field Definition: OMI-Specific

Description: A priori error in ozone profile.

- Field Name: 03AveragingKernel Data Type: HE5T_NATIVE_INT16

Dimensions: nLayer, nLayer, nXtrack, nTimes Range or Valids: Range is -100.0 to 100.0.

Missing Value: -32767
Offset: 0.0d+00
Scale Factor: 1.0d-04
Units: DU/DU
Data Source: PGE

Title: "Retrieval Ozone Averaging Kernels"

Unique Field Definition: OMI-Specific

Description: Retrieval averaging kernels for ozone parameters.

- Field Name: 03InformationContent
Data Type: HE5T_NATIVE_FL0AT
Dimensions: nXtrack,nTimes

Range or Valids: Range is 0.0 to 100.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Ozone Information Content"

Unique Field Definition: OMI-Specific

Description: Information content for ozone parameters.

- Field Name: 03NoiseCorrelationMatrix

Data Type: HE5T_NATIVE_INT16
Dimensions: nElms,nXtrack,nTimes
Range or Valids: Range is -1.0 to 1.0.

Missing Value: -32767
Offset: 0.0d+00
Scale Factor: 1.0d-05
Units: DU
Data Source: PGE

Title: "Ozone Noise Correlation Matrix"

Unique Field Definition: OMI-Specific

Description: Ozone Noise Correlation Matrix, a

symetric matrix

represented by an 1-d array with nElms

elements.

The order of this 1-d array, starts from

the first

row with nLayer-1 elements, append with

the second

row with nLayer-2 elements, so on and so

forth,

down the second last row with one

element.

- Field Name: 03RetrievedProfile
Data Type: HE5T_NATIVE_FLOAT
Dimensions: nLayer,nXtrack,nTimes
Range or Valids: Range is 0 to 100.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "Retrieved Ozone Profile"

Unique Field Definition: OMI-Specific

Description: Retrieved ozone profile.

- Field Name: 03RetrievedProfilePrecision

Data Type: HE5T_NATIVE_FLOAT
Dimensions: nLayer,nXtrack,nTimes
Range or Valids: Range is 0 to 50.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "Retrieval Precision in Ozone Profile"

Unique Field Definition: OMI-Specific

Description: Retrieval precision in ozone profile.

- Field Name: 03RetrievedProfileSolutionError

Data Type: HE5T_NATIVE_FL0AT
Dimensions: nLayer,nXtrack,nTimes
Range or Valids: Range is 0 to 50.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "Retrieval Solution Errors in Ozone

Profile"

Unique Field Definition: OMI-Specific

Description: Retrieval solution errors (root sum

square of random-noise

and smoothing errors) in ozone profile.

- Field Name: 03StratosphericColumn
Data Type: HE5T_NATIVE_FLOAT
Dimensions: nXtrack,nTimes
Range or Valids: Range is 0 to 600.0.

Range of Vactors. Range 13 0 to 000.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "Stratospheric Ozone Column"

Unique Field Definition: OMI-Specific

Description: Stratospheric ozone column.

- Field Name: 03StratosphericColumnPrecision

Data Type: HE5T_NATIVE_FLOAT
Dimensions: nXtrack,nTimes
Range or Valids: Range is 0 to 50.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "Precision in Stratospheric Ozone Column"

Unique Field Definition: OMI-Specific

Description: Precision in stratospheric ozone column.

- Field Name: 03StratosphericColumnSolutionError

Data Type: HE5T_NATIVE_FLOAT
Dimensions: nXtrack,nTimes
Range or Valids: Range is 0 to 50.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "Solution Error in Stratospheric Ozone

Column"

Unique Field Definition: OMI-Specific

Description: Solution error (root sum square of

random-noise

and smoothing errors) in stratospheric

ozone column.

- Field Name: 03TotalColumn
Data Type: HE5T_NATIVE_FL0AT
Dimensions: nXtrack,nTimes

Range or Valids: Range is 0 to 600.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "Total Ozone Column"

Unique Field Definition: OMI-Specific

Description: Total ozone column.

- Field Name: 03TotalColumnPrecision
Data Type: HE5T_NATIVE_FLOAT
Dimensions: nXtrack,nTimes

Dimensions: nXtrack,nTimes
Range or Valids: Range is 0 to 50.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "Precision in Total Ozone Column"

Unique Field Definition: OMI-Specific

Description: Precision in total ozone column.

Field Name: 03TotalColumnSolutionError

Data Type: HE5T_NATIVE_FLOAT
Dimensions: nXtrack,nTimes
Range or Valids: Range is 0 to 50.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "Solution Error in Total Ozone Column"

Unique Field Definition: OMI-Specific

Description: Solution error (root sum square of

random-noise

and smoothing errors) in total ozone

column.

- Field Name: 03TroposphericColumn
Data Type: HE5T_NATIVE_FL0AT
Dimensions: nXtrack,nTimes

Range or Valids: Range is -20 to 150.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "Tropospheric Ozone Column"

Unique Field Definition: OMI-Specific

Description: Tropospheric ozone column.

- Field Name: 03TroposphericColumnPrecision

Data Type: HE5T_NATIVE_FLOAT
Dimensions: nXtrack,nTimes
Range or Valids: Range is 0 to 50.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: DU
Data Source: PGE

Title: "Precision in Tropospheric Ozone Column"

Unique Field Definition: OMI-Specific

Description: Precision in tropospheric ozone column.

- Field Name: 03TroposphericColumnSolutionError

Data Type: HE5T_NATIVE_FLOAT
Dimensions: nXtrack,nTimes
Range or Valids: Range is 0 to 50.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00 Units: DU Data Source: PGE

Title: "Solution Error in Tropospheric Ozone

Column"

Unique Field Definition: OMI-Specific

Description: Solution error (root sum square of

random-noise

and smoothing errors) in tropospheric

ozone column.

- Field Name: OtherGasAPrioriColumnDensity

Data Type: HE5T_NATIVE_FLOAT
Dimensions: nGas,nXtrack,nTimes
Range or Valids: Range is 0 to 1.0e20.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: molecules cm^-2

Data Source: PGE

Title: "Other Gas (non-Ozone) A Priori Vertical

Column Density"

Unique Field Definition: OMI-Specific

Description: A priori in vertical column density for

trace gases (other than ozone).

- Field Name: OtherGasAPrioriColumnDensityError

Data Type: HE5T_NATIVE_FLOAT
Dimensions: nGas,nXtrack,nTimes
Range or Valids: Range is 0 to 1.0e20.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: molecules cm^-2

Data Source: PGE

Title: "Other Gas (non-Ozone) A Priori Error"

Unique Field Definition: OMI-Specific

Description: A priori error in vertical column density

for trace gases (other than ozone).

- Field Name: OtherGasRetrievedVerticalColumnDensity

Data Type: HE5T_NATIVE_FLOAT Dimensions: nGas,nXtrack,nTimes

Range or Valids: Range is -1.0e+20 to 1.0e+20.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: molecules cm^-2

Data Source: PGE

Title: "Retrieved Other Gas (non-Ozone) Vertical

Column Density"

Unique Field Definition: OMI-Specific

Description: Retrieved vertical column density for

trace gases (other than ozone).

- Field Name:

OtherGasRetrievedVerticalColumnDensityPrecision
Data Type: HE5T_NATIVE_FLOAT
Dimensions: nGas,nXtrack,nTimes

Range or Valids: Range is 0.0 to 1.0e+20.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: molecules cm^-2

Data Source: PGE

Title: "Retrieval Precision in Other Gas (non-

Ozone)"

Unique Field Definition: OMI-Specific

Description: Retrieval precision for trace gases

(other than ozone).

- Field Name:

OtherGasRetrievedVerticalColumnDensitySolutionError

Data Type: HE5T_NATIVE_FL0AT
Dimensions: nGas,nXtrack,nTimes
Range or Valids: Range is 0.0 to 1.0e+20.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00 Scale Factor: 1.0d+00

Units: molecules cm^-2

Data Source: PGE

Title: Retrieval Solution Errors in Other Gas

(non-0zone)

Unique Field Definition: OMI-Specific

Description: Retrieval solution errors (root sum

square of random-noise

and smoothing errors) or trace gases

(other than ozone)

- Field Name: ProfileLevelAltitude
Data Type: HE5T NATIVE FLOAT

Dimensions: nLayerp1,nXtrack,nTimes Range or Valids: Range is -1.0 to 100.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: km
Data Source: PGE

Title: "Altitude at each retrieval level"

Unique Field Definition: OMI-Specific

Description: Altitude at layer boundaries (i.e., at

each retrieval level).

atmosphere to surface.

The levels are arranged from top of the

- Field Name: ProfileLevelPressure
Data Type: HE5T_NATIVE_FLOAT
Dimensions: Playern1 pytrack plim

Dimensions: nLayerp1,nXtrack,nTimes Range or Valids: Range is 0.01 to 1100.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: hPa
Data Source: PGE

Title: "Pressure at each retrieval level"

Unique Field Definition: OMI-Specific

Description: Pressure at layer boundaries (i.e., at

each retrieval level).

The levels are arranged from top of the

atmosphere to surface.

- Field Name: ProfileLevelTemperature

Data Type: HE5T_NATIVE_FLOAT

Dimensions: nLayerp1,nXtrack,nTimes Range or Valids: Range is 150. to 350.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: Kelvin
Data Source: PGE

Title: "Temperature at each retrieval level"

Unique Field Definition: OMI-Specific

Description: Temperature at layer boundaries (i.e., at

each retrieval level).

The levels are arranged from top of the

atmosphere to surface.

- Field Name: RMS

Data Type: HE5T_NATIVE_FLOAT

Dimensions: nChannel,nXtrack,nTimes Range or Valids: Range is 0. to 10000.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Ratio of Fitting Residual to Measurement

Error"

Unique Field Definition: OMI-Specific

Description: Ratio of fitting residual to measurement

error.

- Field Name: SimRadiance

Data Type: HE5T_NATIVE_FLOAT

Dimensions: nWavelMax,nXtrack,nTimes

Range or Valids: Range is 0 to 1.0.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Simulated Normalized Radiance: I/F"

Unique Field Definition: OMI-Specific

Description: Simulated normalized radiance: I/F. This

is an

optional datafield, which means it may not be present in the output.

If nWavelMax = -1 in swath attribute, or it is not listed as one of the

swath dimensions, this data field is not in the output file.

- Field Name: SurfaceAlbedo
Data Type: HE5T_NATIVE_FLOAT
Dimensions: nXtrack,nTimes

Range or Valids: Range is -0.2 to 1.2.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Surface Albedo (Zeroth UV2)"

Unique Field Definition: OMI-Specific

Description: Fitted surface albedo (zeroth order in

UV2).

- Field Name: TropopauseIndex
Data Type: HE5T_NATIVE_UINT8
Dimensions: nXtrack,nTimes
Range or Valids: Range is 0 to 100.

Missing Value: 255
Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Index for Tropopause"

Unique Field Definition: OMI-Specific

Description: Index for tropopause level in the ozone

profile.

- Field Name: Wavelength

Data Type: HE5T_NATIVE_FLOAT

Dimensions: nWavelMax,nXtrack,nTimes Range or Valids: Range is 250 to 400.

Missing Value: "-0X1P+100 (C language representation)"

Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: nm
Data Source: PGE

Title: "Wavelengths used in the retrieval"

Unique Field Definition: OMI-Specific

Description: Wavelengths used in the retrieval. This

is an

optional datafield, which means it may not be present in the output.

If nWavelMax = -1 in swath attribute, or it is not listed as one of the

swath dimensions, this data field is not in the output file.

- Field Name: nChannelWavel
Data Type: HE5T_NATIVE_UINT16
Dimensions: nChannel,nXtrack,nTimes
Range or Valids: Range is 0 to 1000.

Missing Value: 65535
Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Number of Wavelengths in Each Fitting

Window"

Unique Field Definition: OMI-Specific

Description: Number of wavelengths in each fitting

window.

Missing Value: 65535
Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Number of Wavelengths in the Fitting"

Unique Field Definition: OMI-Specific

Description: Number of wavelengths used in the

fitting.

- Field Name: nIteration

Data Type: HE5T_NATIVE_UINT8
Dimensions: nXtrack,nTimes
Range or Valids: Range is 0 to 20.

Missing Value: 255
Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Number of Iterations"

Unique Field Definition: OMI-Specific

Description: Number of retrieval iterations.

Dimensions: nTimes

Range or Valids: Range is 0 to 5.

Missing Value: 255
Offset: 0.0d+00
Scale Factor: 1.0d+00
Units: NoUnits
Data Source: PGE

Title: "Number of Small Pixel Columns"

Unique Field Definition: OMI-Specific

Description: Number of small pixel columns.

Core Metadata:

- Metadata Name: AssociatedInstrumentShortName

Mandatory: T
Data Type: VA20
Number of Values: 1

Range or Valids: Valid is "OMI".

Data Source: MCF

Description: Actual is "OMI".

- Metadata Name: AssociatedPlatformShortName

Mandatory: T
Data Type: VA20
Number of Values: 1

Range or Valids: Valid is "Aura".

Data Source: MCF

Description: Actual is "Aura".

- Metadata Name: AssociatedSensorShortName

Mandatory: T
Data Type: VA20
Number of Values: 1

Range or Valids: Valids are "CCD Ultra Violet" and "CCD Visible".

Data Source: MCF

Description: Actual is "CCD Ultra Violet".

- Metadata Name: AutomaticQualityFlag

Mandatory: T

Data Type: VA64 Number of Values: 1

Range or Valids: Valids are "Passed", "Suspect" and "Failed".

Data Source: PGE Description: >

A granule-level quality flag that applies generally to the granule

and specifically to the parameters at the granule level.

Metadata Name: AutomaticQualityFlagExplanation

Mandatory: T
Data Type: VA255
Number of Values: 1

Range or Valids: Not applicable (free format).

Data Source: PGE
Description: >

The definitions of "Passed", "Suspect" and "Failed" should go here.

- Metadata Name: DayNightFlag

Mandatory: T
Data Type: VA5
Number of Values: 1

Range or Valids: Valids are "Day", "Night" and "Both".

Data Source: MCF

Description: Actual is "Day".

- Metadata Name: EquatorCrossingDate

Mandatory: T
Data Type: D
Number of Values: 1

Range or Valids: Range is "1995-01-01" to "2099-12-31".

Data Source: L1B
Description: >

The date of the descending equator crossing in the granule.

- Metadata Name: EquatorCrossingLongitude

Mandatory: T
Data Type: LF
Number of Values: 1

Range or Valids: Range is -180.0d0 to 180.0d0.

Data Source: L1B Description: >

The longitude of the descending equator crossing in the granule.

- Metadata Name: EquatorCrossingTime

Mandatory: T
Data Type: T
Number of Values: 1

Range or Valids: Range is "01:00:0.000000" to "01:59:59.999999".

Data Source: L1B

```
Description:
    The time of the descending equator crossing in the granule.
 – Metadata Name:
                      InputPointer
  Mandatory:
                      Т
                      VA255
   Data Type:
  Number of Values:
                      0 to 10
   Range or Valids:
    Valid file names, each in double quotes, separated by commas, all
    surrounded by curved brackets.
   Data Source:
                      PGE
   Description:
    Example is
    ("OMI-Aura_L1-OML1BRUG_2003m0415t0507-
o01067_v001-2003m0630t230758.he4",
    "OMI-Aura_L1-OML1BIRR_2003m0415t0542-
o01067 v001-2003m0630t185511.he4",
    "", "", "", "", "", "", "", "").
 - Metadata Name:
                      LocalGranuleID
  Mandatory:
   Data Type:
                      VA80
  Number of Values:
                      1
   Range or Valids:
    Range is
    "OMI-Aura_L2-PR0F0Z_1995m0101t0000-
o00000 v003-1995m0101t000000.he5" to
    "OMI-Aura_L2-PR0F0Z_2099m1231t2359-
o99999 v999-2099m1231t235959.he5".
   Data Source:
                      PGE
   Description:
    Example is
    "OMI-Aura_L2-PR0F0Z_2002m0630t2354-
o21434 v001-2003m0515t181917.he5"
    (see Appendix E of Reference 3).
 - Metadata Name:
                      LOCALVERSIONID
  Mandatory:
                      VA60
   Data Type:
  Number of Values:
   Range or Valids:
                      >
    Valids are "RFC1321 MD5 = not yet calculated" and
    "RFC1321 MD5 = [0-9,a-f]{32}"
   Data Source:
                      PCF
   Description:
   MD5 fingerprint of the HDF product file.
                      OperationalQualityFlag
 - Metadata Name:
  Mandatory:
   Data Type:
                      VA20
```

```
Number of Values:
   Range or Valids:
   Valids are "Passed", "Failed", "Being Investigated", "Not
Investigated",
    "Inferred Passed", "Inferred Failed" and "Suspect".
                      L<sub>1</sub>B
   Data Source:
   Description:
                      >
    A granule-level quality flag that applies generally to the granule
    and specifically to the parameters at the granule level.
 – Metadata Name:
                      OperationalQualityFlagExplanation
   Mandatory:
   Data Type:
                      VA255
   Number of Values:
   Range or Valids:
                      Not applicable (free format).
   Data Source:
                      L1B
   Description:
                      >
   The criteria for setting the OperationalQualityFlag should be
stated
    here (this Metadata will not appear in the granule).
- Metadata Name:
                      OPERATIONMODE
   Mandatory:
                      VA20
   Data Type:
   Number of Values:
                      1
   Range or Valids: >
   Valids are "Calibration", "Diagnostic", "Initialization",
"Launch",
    "Normal", "Roll", "Routine", "Safe", "Solar Calibration",
"Standby".
    "Survival" and "Test".
   Data Source:
                      PCF
                      Actual is "Test".
   Description:
 – Metadata Name:
                      OrbitNumber
   Mandatory:
   Data Type:
                      Ι
   Number of Values:
   Range or Valids:
                      Range is 1 to 999999
   Data Source:
                      L<sub>1</sub>B
                      The OMI orbit number.
   Description:
 – Metadata Name:
                      ParameterName
   Mandatory:
                      Т
   Data Type:
                      VA40
   Number of Values:
   Range or Valids:
                      Valid is "Total Column Sulphur Dioxide".
   Data Source:
                      PGE
   Description:
    The measured science parameter expressed in the granule.
```

- Metadata Name: PGEVERSION

Mandatory: T
Data Type: VA10
Number of Values: 1

Range or Valids: Range is "0.0.0" to "9.9.99".

Data Source: PCF

Description: Actual is "1.0.1".

- Metadata Name: ProductionDateTime

Mandatory: T
Data Type: DT
Number of Values: 1
Range or Valids: >

"2003-01-01T00:00:00.000Z" to "2099-12-31T24:59:59.999Z"

Data Source: TK

Description: The date and time of the Level 2 processing.

- Metadata Name: QAPercentCloudCover

Mandatory: T
Data Type: I
Number of Values: 1

Range or Valids: Range is 0 to 100

Data Source: PGE
Description: >

The percent of the data in the granule that have cloud cover.

- Metadata Name: QAPercentInterpolatedData

Mandatory: T
Data Type: I
Number of Values: 1

Range or Valids: Range is 0 to 100

Data Source: PGE Description: >

The percent of the data in the granule that are interpolated.

- Metadata Name: QAPercentMissingData

Mandatory: T
Data Type: I
Number of Values: 1

Range or Valids: Range is 0 to 100.

Data Source: PGE Description: >

The percent of the data in the granule that are missing.

- Metadata Name: QAPercentOutofBoundsData

Mandatory: T
Data Type: I
Number of Values: 1

Range or Valids: Range is 0 to 100.

Data Source: PGE
Description: >

The percent of the data in the granule that are out of bounds data.

- Metadata Name: RangeBeginningDate

Mandatory: T
Data Type: D
Number of Values: 1

Range or Valids: Range is "1995-01-01" to "2099-12-31".

Data Source: L1B

Description: The year, month and day when the granule began.

- Metadata Name: RangeBeginningTime

Mandatory: T
Data Type: T
Number of Values: 1

Range or Valids: Range is "00:00:00.000000" to "23:59:59.999999".

Data Source: L1B Description: >

The hour, minute, second and fraction of a second when the granule

began.

Metadata Name: RangeEndingDate

Mandatory: T
Data Type: D
Number of Values: 1

Range or Valids: Range is "1995-01-01" to "2099-12-31".

Data Source: L1B

Description: The year, month and day when the granule ended.

- Metadata Name: RangeEndingTime

Mandatory: T
Data Type: T
Number of Values: 1

Range or Valids: Range is "00:00:00.000000" to "23:59:59.999999".

Data Source: L1B Description: >

The hour, minute, second and fraction of a second when the granule

ended.

- Metadata Name: REPROCESSINGACTUAL

Mandatory: T
Data Type: VA20
Number of Values: 1
Range or Valids: >

Valids are "processed 1 time", "processed 2 times", etc...

Data Source: PCF
Description: >

An indication of what reprocessing has been performed on the

granule.

– Metadata Name: ReprocessingPlanned Mandatory: **VA45** Data Type: Number of Values: 1 Range or Valids: > Valids are "no further update anticipated", "further update is anticipated" and "further update anticipated using enhanced PGE". Data Source: Description: Actual is "further update is anticipated". - Metadata Name: ScienceQualityFlag Mandatory: Т Data Type: **VA20** Number of Values: 1 Range or Valids: Valids are "Passed", "Failed", "Being Investigated", "Not Investigated", "Inferred Passed", "Inferred Failed" and "Suspect". Data Source: Actual is "Not Investigated". Description: - Metadata Name: ScienceQualityFlagExplanation Mandatory: Data Type: VA255 Number of Values: Range or Valids: Not applicable (free format). Data Source: DP Description: An explanation of the criteria used to set the science quality flag should go here. - Metadata Name: ShortName Mandatory: VA8 Data Type: Number of Values: Range or Valids: Valid is "PROFOZ". Data Source: MCF Description: Actual is "PROFOZ". - Metadata Name: SizeMBECSDataGranule Mandatory: F LF Data Type: Number of Values: Range or Valids: Range is 0.00d+00 to 1.00d+04. Data Source:

DSS

>

Description:

The volume of data contained in the granule in Mb (this Metadata will not appear in the granule).

- Metadata Name: VersionID

Mandatory: T
Data Type: SI
Number of Values: 1

Range or Valids: Range is 0 to 999.

Data Source: MCF

Description: Actual is 1 for test and pre-launch.

Product Specific Attributes:

- Metadata Name: EndBlockNr

Mandatory: T Data Type: SI

Number of Values: 1 to 500

Range or Valids: Range is 1 to 50.

Data Source: L1B

Description: The number of the NOSE end block along the

track.

- Metadata Name: PathNr

Mandatory: T Data Type: I

Number of Values: 1 to 500

Range or Valids: Range is 1 to 466.

Data Source: L1B

Description: Number of the NOSE path within the repeat cycle.

- Metadata Name: SolarEclipse

Mandatory: T
Data Type: VA10
Number of Values: 1

Range or Valids: Valids are "TRUE" and "FALSE".

Data Source: L1B
Description: >

The indicator that during part of the measurements a solar eclipse

occurred.

Metadata Name: SouthAtlanticAnomalyCrossing

Mandatory: T
Data Type: VA10
Number of Values: 1

Range or Valids: Valids are "TRUE" and "FALSE".

Data Source: L1B Description: >

The indicator that during part of the measurements the spacecraft

was in the SAA.

- Metadata Name: StartBlockNr

Mandatory: T Data Type: SI

Number of Values: 1 to 500

Range or Valids: Range is 1 to 50.

Data Source: L1B

Description: Number of the NOSE start block along the track.

Archived Metadata:

- Metadata Name: ESDTDescriptorRevision

Mandatory: T
Data Type: VA20
Number of Values: 1

Range or Valids: Range is "0.0.0" to "9.9.99".

Data Source: MCF Description: >

This is the version of the ESDT descriptor file as determined by ECS.

- Metadata Name: LongName

Mandatory: T
Data Type: VA80
Number of Values: 1
Range or Valids: >

Valid is

"OMI/Aura Vertical Ozone (03) Profile 1-Orbit L2 Swath 13x48 km"

Data Source: MCF
Description: >
 Actual is

"OMI/Aura Vertical Ozone (03) Profile 1-Orbit L2 Swath 13x48 km" (see Section 7.0 of Reference 2).

References: >

1. Liu, X., Chance, K., Sioris, C. E., Spurr, R. J. D., Kurosu, T. P.,

Martin, R. V., and Newchurch, M. J.: "Ozone profile and tropospheric

ozone retrievals from Global Ozone Monitoring Experiment:

description and validation", J. Geophys. Res., 110, D20307, 20310.21029/22005JD006240, 2005.

and

Liu, X., Bhartia, P. K., Chance, K., Spurr, R. J. D., and Kurosu, T. P.:

"Ozone profile retrievals from the Ozone Monitoring Instrument", Atmos.

Chem. Phys. Discuss., 9, 22693-22738, 2009.

- 2. "HDF-EOS Aura File Format Guidelines"
 (OMI-AURA-DATA-GUIDE, Version 1.3, 16 October 2003)
- 3. "OMI Science Software Delivery Guide for Version 0.9" (OMI-SSDG-0.9.9, Version 0.9.9, 21 October 2003)
- 4. "OMI GDPS Input/Output Data Specification (IODS) Volume 2" (OMI-GDPS-IODS-2, SD-OMIE-7200-DS-467, 9 April 2003)
- 5. "Release 6A Implementation Earth Science Data Model for the ECS Project"

(420-TP-022-002, June 2001)

(http://edhs1.gsfc.nasa.gov/waisdata/rel6/html/tp4202202.html and http://edhs1.gsfc.nasa.gov/waisdata/rel6/html/tp42022_adds.html)

6. "OMI L2 - L4 Metadata Reference Guide"
 (3 July 2002)
 (https://omiwww.gsfc.nasa.gov/mlinda/OMImetadataRefGuide.html)